

Fragile

Jaume Ramírez

marset

The Fragile lamp is a mix of geometric shapes. A cone and a sphere are arranged to hold a cylinder that emits ambient light from below. In its form, we find remnants of the past; in the material, we find emotion. The glass not only reveals the light source; it also speaks of purity, lightness and how this design blends in with its surroundings. Its structure seems to stand effortlessly, a very serious feat in which everything is in plain sight. The cylinder shades its warm, diffused and gradual light.





Fragile 16

Code	Finish	CCT	Dimming
Structure			
A724-110-17-22K	Aluminium	2200K	ELV/Triac
A724-110-17-27K	Aluminium	2700K	ELV/Triac
A724-110-39-22K	Black (RAL 9005)	2200K	ELV/Triac
A724-110-39-27K	Black (RAL 9005)	2700K	ELV/Triac
A724-110-35-22K	White (RAL 9010)	2200K	ELV/Triac
A724-110-35-27K	White (RAL 9010)	2700K	ELV/Triac
A724-111-17-22K	Aluminium	2200K	0-10V
A724-111-17-27K	Aluminium	2700K	0-10V
A724-111-39-22K	Black (RAL 9005)	2200K	0-10V
A724-111-39-27K	Black (RAL 9005)	2700K	0-10V
A724-111-35-22K	White (RAL 9010)	2200K	0-10V
A724-111-35-27K	White (RAL 9010)	2700K	0-10V
Shade			
Cone			
A724-040-50	Transparent		
Sphere			
A724-041-50	Transparent		

Materials
Diffuser: Blown glass
Base: Aluminium

Dimmable: Yes
Integrated dimmer: Yes
Dimming protocols: ELV/Triac (Min. 3%)
0-10V (Min. 0.1%)

Product details
Cable length: 118.1"
Wire installation: Hardwired
Color cord: Black
Canopy color: Black

LED included

Electrical

ELV/Triac
Electrical Rating: 120Vac 60Hz 6.7W
Light source: 380lm
CCT: 2200K / 2700K
CRI: 80 / 90

0-10V
Electrical Rating: 120Vac 60Hz 6.7W
Light source: 380lm
CCT: 2200K / 2700K
CRI: 80 / 90

Dimmmable


Dry locations only

Fragile 16 compositions

Structure
A724-110-XX-XXK 1 unit
A724-111-XX-XXK


Cone shade
A724-040-XX 1 unit

Sphere shade
A724-041-XX 1 unit




Structure
A724-110-XX-XXK 1 unit
A724-111-XX-XXK

Cone shade
A724-040-XX 1 unit



Structure
A724-110-XX-XXK 1 unit
A724-111-XX-XXK

Sphere shade
A724-041-XX 1 unit



Fragile 16 - 24V

Code	Finish	CCT
Structure		
A724-118-17-22K	Aluminium	2200K
A724-118-17-27K	Aluminium	2700K
A724-118-39-22K	Black (RAL 9005)	2200K
A724-118-39-27K	Black (RAL 9005)	2700K
A724-118-35-22K	White (RAL 9010)	2200K
A724-118-35-27K	White (RAL 9010)	2700K
Shade		
Cone		
A724-040-50	Transparent	
Sphere		
A724-041-50	Transparent	

Materials
Diffuser: Blown glass
Base: Aluminium

Dimmable: Yes
Integrated dimmer: No
Dimming protocols: It depends on the purchased power supply.

Product details
Cable length: 118.1"
Wire installation: Hardwired
Color cord: Black

Electrical
CCT: 2200K
Electrical Rating: 24Vdc 4.8W
Light source: 380lm
CRI: 80

CCT: 2700K
Electrical Rating: 24Vdc 3.7W
Light source: 380lm
CRI: 90

Product notes: 24V remote power supply to be ordered separately.

LED included

Dimmmable

Under approval process.


Dry locations only

Fragile 16 - 24V compositions

Structure
A724-118-XX-XXK 1 unit


Cone shade
A724-040-XX 1 unit

Sphere shade
A724-041-XX 1 unit




Structure
A724-118-XX-XXK 1 unit

Cone shade
A724-040-XX 1 unit



Structure
A724-118-XX-XXK 1 unit

Sphere shade
A724-041-XX 1 unit



Circular Cluster Canopy 90W 24V ELV/Triac/0-10V

Code	Finish
A666-259-39	Black

Materials
Structure: Painted iron


Product type: Accessory
INPUT: 120-277VAC 50/60Hz
OUTPUT: CV 24V DC 90W max.

Weight: Net 6.6 lb – Gross 7.7 lb
Package: 16.14 x 16.14 x 3.15 " - 7.7 lb – VOL - 0.47 ft³
Product notes: Canopy for 24V luminaires.
Total wattage of all connected fixtures must not exceed canopy or driver wattage. Make selections accordingly.

Wire installation: Hardwired
Canopy color: Black - Entry points: 3

Dimmable: Yes
Integrated dimmer: No
Dimming protocols: ELV / Triac / 0-10V

Dimmable



Circular Cluster Canopy 180W 24V ELV/Triac/0-10V

Code
A666-260-39

Finish
● Black

Materials
Structure: Painted iron


Product type: Accessory
Input: 120-277VAC 50/60Hz
Output: CV 24V DC 180W max.

Weight: Net 8.4 lb – Gross 9.5 lb
Package: 16.14 x 16.14 x 3.15 " - 9.5 lb – VOL - 0.47 ft³
Product notes: Canopy for 24V luminaires.
Total wattage of all connected fixtures must not exceed canopy or driver wattage. Make selections accordingly.

Wire installation: Hardwired
Canopy color: Black - Entry points: 5

Dimmable: Yes
Integrated dimmer: No
Dimming protocols: ELV / Triac / 0-10V

Dimmable



* Canopies with more entry points available under request

Accessories Fragile

Hook Accessory


Code
A693-007

Finish
● Black

Materials
Structure: Painted iron

Product type: Accessory
Weight: Net 0.02 lb – Gross 0.02 lb
Package: 0.8 x 0.8 x 2 " - 0.02 lb – VOL - 0.07 ft³

Product notes: Accessory to guide the cable.



⚠ **WARNING.** California Proposition 65 Warning for California Consumers. This product can expose you to chemicals including wood dust and lead which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

info@marset.com
www.marset.com

Download

Photometric data file (LDT or IES)
2D, 3D, Photometric Data
Assembly instructions

Collection

